

QU∧NTUM DISINFECTION™

DISINFECTION

- removes more than 99% of bacteria from the RO water

WATER FLOWS

up to 0.5 GPM

PERFORMANCE

- water volume: up to 3,000 gallons of use

- contains high quality coconut shell GAC that reduces:

- odor and organics

CERTIFICATIONS

Quantum Disinfection™ is:

- a NSF Certified Component to NSF/ANSI 42 for material requirements only (Certificate #: C0292640-01)

- tested by IAPMO to NSF/ANSI 61 (Certificate #: 23033)

- Certified MOH - China (Certificate #: 2015KF2513)

NO CHEMICALS. NO POWER. NO PATHOGENS

MAIN USE

- post RO for bacteria reduction (E. coli)

Application	Point-of-Use
Power Requirements	None
Main Use	- Water Disinfection - Teste & Odor Removal
Flow rates	0.5 GPM 2 L/min
Unit Dimensions	6 x 2 inch 15 x 5 cm
Min Operating Pressure	25 psi 1.7 bar
Max Operating Pressure	125 psi 8.6 bar
Expected Life	3,000 gallons 11,100 liters
Operating Temperature	41 - 100 °F 5 - 38 °C
Disinfection Capacity	> 99%
Inlet/Outlet Connection Size	FTP - 1/4 inch
Replaceable Cartridge	Yes



Contact



info@claire-technologies.com



(984) 242 0855



www.claire-technologies.com



627 Distribution Drive #E Morrisville, NC 27560



